



## Waterproofing **Deckguard® Tack Coat**

### Product Description

Deckguard® Tack Coat is a high solids, single component, polymer modified bitumen adhesive designed to provide the best possible bond of asphalt overlays to the Deckguard™ Membrane.

### Applications

Deckguard® Tack Coat is designed for use with Deckguard™ Membrane and hot-applied DOT asphalts.

### Surface Preparation

Remove any deleterious material from Deckguard® Membrane prior to applying Deckguard® Tack Coat.

### Mixing Instructions

Deckguard® Tack Coat is a single component product. No mixing required.

### Application Recommendation

Heat tack coat to 400°F in a double boiler, and then apply by mop, brush or squeegee.

### Safety

Keep away from sparks and flame. Read Safety Data Sheet before using.

### Shelf Life

Shelf life is up to three years in sealed, unopened factory containers under normal storage conditions of 55°F to 95°F.

### Deckguard® Tack Coat Data

Property	Test Method	Criteria
Color		Black
Specific Gravity at 25° C		1.02
Penetration at 77° F	ASTM D5	15 - 40
Weight per Gallon at 60° F		8.5 lbs.
Flash Point, C.O.C.		550° F min
Odor		Tar

### Chemical Composition

Bitumen based polymer modified mastic

### Warranty

Provided upon request.

### The D.S. Brown Company

Founded in 1890 and based in North Baltimore, Ohio, USA, The D.S. Brown Company is a worldwide designer, manufacturer and supplier of engineered products for the highway and bridge construction markets.